

Q-SC-P620 Powered Horn Speaker



Highly Intelligible Speaker with built-in Digital Power Amplifier

Q-SC-P620 Powered Horn Speaker

The Q-SC-P620 is a highly intelligible and compact horn speaker with a built-in 20W digital power amplifier, that provides public address announcement and remote paging via network video surveillance applications. This powered horn speaker can operate at extreme temperature. It comes with powder-coated finish and stainless steel screws to ensure its weatherproof capability. Ideal choice for both indoor and outdoor application at restricted facilities, train stations, airports and many more.

Key Features

- Integrated 20W power amplifier which utilises latest Class D technology
- > Switchable Gain: 8dB, 16dB, 24dB & 32dB
- > Internal volume control to allow on-site tuning
- ➤ Integration to CCTV systems possible with the majority of IP CCTV systems equipped with an audio line output
- > Weatherproof to IP65 rating














Network Camera Configuration



Specification

Power Source 12V DC, 2A (DC Socket "+" Type A: 5.5 x 2.1mm) Power Consumption 15W (1.25A) at Rated output 25W (2.10A) at Maximum output Input 0 dB*, 10kΩ, Unbalanced (RCA plug) Signal Gain 8, 16, 24, 32dB (Factory pre-set to 16dB) Volume Adjustment Internal volume control (Factory pre-set to max. position) Sound Pressure Level 113dB (1W, 1m at 500Hz to 2.5kHz peak level) Max. SPL (above 120dB) Frequency Response 250 - 10,000 Hz Operating Temperature -20C to +55C (must be free from dew condensation) Dust/Water Protection IP 65 Finish Hom Flare: HIPS resin, white (RAL 9010 equivalent) Reflector Hom & Case: ABS resin, white (RAL 9010 equivalent) Bracket, Screws & Bolts: Stainless Steel Cable Cord Length: 2m Flying Lead (RCA plug) & DC socket ("+") Dimensions 292 (W) x 230 (H) x 280 (D) mm Weight Approx. 1.8kg Option AD-5000-2 (LTE24E-S2-1) AC Adapter		
25W (2.10A) at Maximum output	Power Source	12V DC, 2A (DC Socket "+" Type A: 5.5 x 2.1mm)
Input O dB*, 10kΩ, Unbalanced (RCA plug)	Power Consumption	15W (1.25A) at Rated output
Signal Gain 8, 16, 24, 32dB (Factory pre-set to 16dB) Volume Adjustment Internal volume control (Factory pre-set to max. position) Sound Pressure Level 113dB (1W, 1m at 500Hz to 2.5kHz peak level) Max. SPL (above 120dB) Frequency Response 250 - 10,000 Hz Operating Temperature -20C to +55C (must be free from dew condensation) Dust/Water Protection IP 65 Finish Hom Flare: HIPS resin, white (FAL 9010 equivalent) Reflector Hom & Case: ABS resin, white (FAL 9010 equivalent) Bracket, Screws & Bolts: Stainless Steel Cable Cord Length: 2m Flying Lead (RCA plug) & DC socket ("+") Dimensions 292 (W) x 230 (H) x 280 (D) mm Weight Approx. 1.8kg		25W (2.10A) at Maximum output
Volume Adjustment Internal volume control (Factory pre-set to max. position) Sound Pressure Level 113dB (1W, 1m at 500Hz to 2.5kHz peak level) Max. SPL (above 120dB) Frequency Response 250 - 10,000 Hz Operating Temperature -20C to +55C (must be free from dew condensation) Dust/Water Protection IP 65 Finish Horn Flare: HIPS resin, white (RAL 9010 equivalent) Reflector Horn & Case: ABS resin, white (RAL 9010 equivalent) Bracket, Screws & Bolts: Stainless Steel Cable Cord Length: 2m Flying Lead (RCA plug) & DC socket ("+") Dimensions 292 (W) x 230 (H) x 280 (D) mm Weight Approx. 1.8kg	Input	0 dB*, 10kΩ, Unbalanced (RCA plug)
Sound Pressure Level 113dB (1W, 1m at 500Hz to 2.5kHz peak level) Max. SPL (above 120dB) Frequency Response 250 - 10,000 Hz Operating Temperature -20C to +55C (must be free from dew condensation) Dust/Water Protection IP 65 Finish Hom Flare: HIPS resin, white (RAL 9010 equivalent) Reflector Hom & Case: ABS resin, white (RAL 9010 equivalent) Bracket, Screws & Bolts: Stainless Steel Cable Cord Length: 2m Flying Lead (RCA plug) & DC socket ("+") Dimensions 292 (W) x 230 (H) x 280 (D) mm Weight Approx. 1.8kg	Signal Gain	8, 16, 24, 32dB (Factory pre-set to 16dB)
Max. SPL (above 120dB) Frequency Response 250 - 10,000 Hz Operating Temperature -20C to +55C (must be free from dew condensation) Dust/Water Protection IP 65 Finish Horn Flare: HIPS resin, white (RAL 9010 equivalent) Reflector Horn & Case: ABS resin, white (RAL 9010 equivalent) Bracket, Screws & Bolts: Stainless Steel Cable Cord Length: 2m Flying Lead (RCA plug) & DC socket ("+") Dimensions 292 (W) x 230 (H) x 280 (D) mm Weight Approx. 1.8kg	Volume Adjustment	Internal volume control (Factory pre-set to max. position)
Frequency Response 250 - 10,000 Hz Operating Temperature -20C to +55C (must be free from dew condensation) Dust/Water Protection IP 65 Finish Hom Flare: HIPS resin, white (RAL 9010 equivalent) Reflector Hom & Case: ABS resin, white (RAL 9010 equivalent) Bracket, Screws & Bolts: Stainless Steel Cable Cord Length: 2m Flying Lead (RCA plug) & DC socket ("+") Dimensions 292 (W) x 230 (H) x 280 (D) mm Weight Approx. 1.8kg	Sound Pressure Level	113dB (1W, 1m at 500Hz to 2.5kHz peak level)
Operating Temperature -20C to +55C (must be free from dew condensation) Dust/Water Protection Finish Hom Flare: HIPS resin, white (RAL 9010 equivalent) Reflector Hom & Case: ABS resin, white (RAL 9010 equivalent) Bracket, Screws & Bolts: Stainless Steel Cable Cord Length: 2m Flying Lead (RCA plug) & DC socket ("+") Dimensions 292 (W) x 230 (H) x 280 (D) mm Weight Approx. 1.8kg		Max. SPL (above 120dB)
Dust/Water Protection Finish Horn Flare: HIPS resin, white (RAL 9010 equivalent) Reflector Horn & Case: ABS resin, white (RAL 9010 equivalent) Bracket, Screws & Bolts: Stainless Steel Cable Cord Length: 2m Flying Lead (RCA plug) & DC socket ("+") Dimensions 292 (W) x 230 (H) x 280 (D) mm Weight Approx. 1.8kg	Frequency Response	250 - 10,000 Hz
Finish Hom Flare: HIPS resin, white (RAL 9010 equivalent) Reflector Hom & Case: ABS resin, white (RAL 9010 equivalent) Bracket, Screws & Bolts: Stainless Steel Cable Cord Length: 2m Flying Lead (RCA plug) & DC socket ("+") Dimensions 292 (W) x 230 (H) x 280 (D) mm Weight Approx. 1.8kg	Operating Temperature	-20C to +55C (must be free from dew condensation)
Reflector Horn & Case: ABS resin, white (RAL9010 equivalent) Bracket, Screws & Bolts: Stainless Steel Cable Cord Length: 2m Flying Lead (RCA plug) & DC socket ("+") Dimensions 292 (W) x 230 (H) x 280 (D) mm Weight Approx. 1.8kg	Dust/Water Protection	IP 65
Bracket, Screws & Bolts: Stainless Steel Cable Cord Length: 2m Flying Lead (RCAplug) & DC socket ("+") Dimensions 292 (W) x 230 (H) x 280 (D) mm Weight Approx. 1.8kg	Finish	Horn Flare: HIPS resin, white (RAL 9010 equivalent)
Cable CordLength: 2m Flying Lead (RCAplug) & DC socket ("+")Dimensions292 (W) x 230 (H) x 280 (D) mmWeightApprox. 1.8kg		Reflector Horn & Case: ABS resin, white (RAL9010 equivalent)
Dimensions 292 (W) x 230 (H) x 280 (D) mm Weight Approx. 1.8kg		Bracket, Screws & Bolts: Stainless Steel
Weight Approx. 1.8kg	Cable Cord	Length: 2m Flying Lead (RCA plug) & DC socket ("+")
Troight and the second	Dimensions	292 (W) x 230 (H) x 280 (D) mm
Option AD-5000-2 (LTE24E-S2-1) AC Adapter	Weight	Approx. 1.8kg
	Option	AD-5000-2 (LTE24E-S2-1) AC Adapter



